

# Econometric model for forecasting electricity demand of industry and construction sectors in Vietnam to 2030

Viet-Cuong VO<sup>1,\*</sup>, Hoang-Phuong NGUYEN<sup>1,2</sup>, Le-Duy-Luan NGUYEN<sup>3</sup>, Van-Hung PHAM<sup>1</sup>



Use your smartphone to scan this QR code and download this article

<sup>1</sup>Ho Chi Minh City University of Technology and Education, No.1, Vo Van Ngan Street, HCMC, Vietnam

<sup>2</sup>Tien Giang University, No.119, Ap Bac Street, Ward 5, My Tho, Tien Giang

<sup>3</sup>University of Architecture Ho Chi Minh City, No 196, Pasteur Street, District 3, HCMC, Vietnam

## Correspondence

**Viet-Cuong VO**, Ho Chi Minh City University of Technology and Education, No.1, Vo Van Ngan Street, HCMC, Vietnam

Email: cuongvv@hcmute.edu.vn

## History

- Received: 15-12-2019
- Accepted: 13-3-2020
- Published: 31-3-2020

DOI : 10.32508/stdjet.v3i1.646



Check for updates

## Copyright

© VNU-HCM Press. This is an open-access article distributed under the terms of the Creative Commons Attribution 4.0 International license.



## ABSTRACT

An accurate forecasting for long-term electricity demand make a major role to the planning of the power system in any country. Vietnam is one of the most economic developing country in the world, and its electricity demand has been increased dramatically high of about 15%/y for last three decades. Contribution of industry and construction sectors in GDP have been increasing year by year, and are currently holding the leading position of the largest consumers with more than 50% sharing in national electricity consumption proportion. How to estimate correctly electricity consumption of these sectors takes a crucial contribution for the planning of the power system. This paper applies econometric model with Cobb Douglas production function - a top down method to forecast electricity demand of the industry and construction sectors in Vietnam to 2030. Four variables used are value of the sectors in GDP, income per person, proportion of electricity consumption of the sectors in total, and electric price. Forecasted results show that the proposed method has a quite low MAPE of 7.66% for a long-term forecasting. Variable of electric price does not affect to the demand. This is a very critical result of the study for authority governors in Vietnam. In base scenario of the GDP and the income per person, the forecasted electricity demands of the sectors are 112,853 GWh, 172,691 GWh, and 242,027 GWh in 2020, 2025, 2030, respectively. In high scenario one, the demands are 115,947 GWh, 181,591 GWh, and 257,272 GWh, respectively. The above values in the high scenario are less than from 9.0% to 15.8 % of that of the based of in the Revised version of master plan NQ. VII.

**Key words:** Forecast, Econometric model, Electricity demand, Cobb Douglas production function, Industry & construction sectors

## INTRODUCTION

An accurate forecasting for long-term electric loads can make a major contribution to the planning of a national power system. Forecasting electric load demand in consideration with its definite duration could be applied to build up long-term maintenance schedules, to establish the development and construction plan for new power-facilities, and expansion plan for transmission and distribution systems. The accuracy of a long-term forecasting model will lead to the feasibility and rationality of the future production and distribution development plan of power enterprises. An overestimating of demand can result unexpected effects on financial terms; while an underestimating will not only lead to the lack of power supply, but also injure the satisfactory of consumers or even damage to the national economy and society. Therefore, forecasting power demand for industry and construction sectors is an important compulsory.

Industry and construction sectors are the two biggest sectors which contribute more than 40% of Vietnam's gross domestic production (GDP). In order to meet

that contribution, more than 50% of Vietnam electricity consumption has been delivered to that two sectors; in which some huge consumers could be identified as cement industry, steel - making factories, food processing facilities and beverage manufacturers, textile industry, etc...

Consumption of those industries has been increased significantly in recent years<sup>1</sup>.

Worldwide-studies on forecasting long-term electric load demand over the last decades are mainly focused on applying artificial neural network (ANN-based models)<sup>2</sup>, and econometric model (i.e. Cobb Douglas) into planning process<sup>3</sup>. ANN-based models have been implemented successfully in many countries due to its flexibility, high accuracy in terms of forecasting, good adaptation and processing ability on fluctuant data. However, when applying into Vietnam's context, ANN cannot prove its mentioned strengths because historical data on national and partial electric consumption was not fully recorded.

Cobb Douglas production function is an econometric approach which combines different statistical techniques and economic theories to forecast long-term

**Cite this article :** VO V, NGUYEN H, NGUYEN L, PHAM V. Econometric model for forecasting electricity demand of industry and construction sectors in Vietnam to 2030. *Sci. Tech. Dev. J. – Engineering and Technology*; 3(1):316-325.

power demand and electricity consumption. This method has been widely applied in researches of developing countries, such as Malaysia<sup>4</sup>, Pakistan<sup>5</sup>, and China<sup>6</sup>, etc. The strengths of Cobb Douglas production function are that: (1) it provides detail information about the stable and the changeability of variables and forecasted values; (2) it could be used to investigate the influential factors or variables impacting on forecasted results; and (3) it is a practical method which is easy to be analyzed and calculated<sup>7</sup>. Despite all these advantages, there is no record about experience on applying this method in forecasting long-term electricity demand for the industry and construction sectors.

## METHOD AND DATA

### Cobb Douglas production function

A Cobb Douglas production function is expressed in a non-linear form as<sup>2</sup>:

$$EC_t = \phi G_t^{\beta_1} I_t^{\beta_2} X_t^{\beta_3} P_t^{\beta_4} \quad (1)$$

Where  $EC_t$  is the consumption of industry and construction sectors in the year  $t$ ;  $G_t$ ,  $I_t$ ,  $X_t$ , and  $P_t$  are represented for the GDP of industry and construction sectors, income per person (US\$/person), proportion of industry and construction sectors' electricity consumption in total, and electric tariff in the year  $t$ , respectively. The technological parameter is indicated by  $\phi$ ;  $\beta_i$  are returns to scale linked with the four variables.

A logarithmic transformation is applied for two sides of the equation (1) to linearize it to become a linear form as:

$$\ln EC_t = \beta_0 + \beta_1 \ln G_t + \beta_2 \ln I_t + \beta_3 \ln X_t + \beta_4 \ln P_t \quad (2)$$

### Testing

In order to evaluate the accuracy of econometric model, many testing methods have been recorded. Testing methods are computed with aims to maximize the accuracy and reliability of forecasting equation. For those researches proving the causality between variables, the date in time series should be tested the stationary (Augmented Dickey Fuller (ADF) or Phillips-Perron (P-P)) to avoid the spurious regression. After stationary test, the causality between variables is proven by using Granger causality test. For forecasting purpose, stationary test only is enough.

### Stationary test

In order to ensure the sustainability of this study, two unit root test namely ADF and P-P are employed to test the stationary of prediction function. They are

employed to avoid the spurious regression or non-sense regression when applying regression algorithm onto a non-stationary time series data. If there are some non-stationary series, to solve the problem, the first difference ( $\Delta$ ) of the series is done, then eliminating inappropriate variables. If all series are non-stationary, it leads to take the first difference of all variables, then removes the primary features of the series. However, it leads to the low  $R^2$  in regressing. The low  $R^2$  means the low accuracy of the prediction. To avoid the low of  $R^2$ , co-integration test is conducted.

### Cointegration test

Engle and Granger (1987)<sup>8</sup> supposed the linear combination between non-stationary time series can be a stationary series and these non-stationary time series are co-integrated. The non-stationary linear combination is called co-integration equation and can be explained as the balance relationship between variables in long-term. Therefore, if variables co-integrate, the regression can be conducted. In this article, Johansen trace test is utilized to test the co-integration. In the Trace test (T-test), there are some hypotheses  $H_0$  listed as follow: "None", means there is no co-integration; "At most 1; 2; 3...", means there is 1, or 2, or 3 co-integrations. To decide if we should reject or accept hypothesis  $H_0$ , Trace Statistic value and Critical Value of 5% are compared. If Trace Statistic < Critical Value, accept  $H_0$ ; if Trace Statistic > Critical Value, reject  $H_0$ .

### $R^2$ test (R square) and p-test

$R^2$  plays an important role to evaluate the impact of dependent variables to independent variables. The condition to choose the impact factors of function is that  $R^2$  is approximately 1. For example, if the value of  $R^2$  is 0.997953, then it means that 99.8% dependent variables have impact on independent ones. However, in order to decide if any independent variable is needed to function, then a p-value test must be conducted. The condition to choose the value of p-value is p-value  $\leq 0.05$ . If any independent variable has its p-value bigger than 0.05 ( $p > 0.05$ ), then that variable must be eliminated and testing process must be iterated to get higher accurate forecasted results.

### MAPE test

Beside the stationary and co-integration test, a feasibility test based on historical time-series data of prediction function will be conducted by employing a Mean Absolute Percentage Error (MAPE) method to measure the accuracy of prediction. It has a fact that

a relative error of a forecast can be measured by a MAPE, which could be expressed as:

$$MAPE = \frac{1}{N} \sum_{n=1}^N \left| \frac{A_n - F_n}{A_n} \right| 100\% \quad (3)$$

Where  $A_n$  is recorded consumption of the year  $n$ ;  $F_n$  is forecasted consumption of the year  $n$ . It is noted that MAPE has an opposite principle with  $R^2$  as a lower computed MAPE will lead to higher reliable prediction, while a higher  $R^2$  could act the same meaning. MAPE is launched in this paper to evaluate the accuracy of forecast function and to compare with tolerance indicator values.

### Forecasting

After building a standard function for predicting the electricity consumption of Vietnam industry and construction sectors, variable data and its corresponding historical data will then be obtained to import to the function. The consumption demand of Vietnam industry and construction sectors in the year 2020, 2025, and 2030 will be forecasted correspondingly afterward.

### Data

#### GDP of industry and construction sectors

Vietnam is remarked as one of the most rapid growing countries in the world with the GDP growth rate at about 6.5%/year in recent years; in which industry and construction sectors is the biggest contributor with the GDP growth rate is still maintained at a higher rate than the GDP of the entire economics. In 2011, the GDP growth rate of industry and construction sectors reached 6.68% while the value of the national economics is recorded at 6.24%; corresponding values in 2012 are 5.75% and 5.25%, 5.5% and 5.4% in 2013. The average values of the last three years are 6% and 5.4%, correspondingly. There are three growing scenarios for Vietnam's GDP to 2035 have been released; in which the GDP growth rates in the low scenario are forecasted to reach 6.5%/year in 2016-2025 and 6%/year from 2026 to 2035<sup>9</sup>. These results are closely similar to forecasted growth rate of electricity consumption demands which are released by the Revised version of Master Plan N0. VII for Power System in Vietnam (PDP.VII rev.)<sup>9</sup>. This similarity can be used to demonstrated that GDP and electricity consumption demand could have a somehow correlation. The GDP data of industry and construction sectors will be cited from the PDP.VII rev.

### Income

Income per person and person's electricity demand are confidentially believed to have a linear relation as

the increase of person's incomes will lead to the higher needs of electric appliances and corresponding consumptions to improve the living conditions. For example at a low income condition, air conditioner and electric water heater could be dispensable. However, when the income is improved on enough to cover a high-cost electric bill, then they might be purchased to meet the demand of the house owners. It definitely leads to the more pressure on electric supply conditions. Therefore, the person's income is launched as an essential variable of forecasting model in this paper to quantify its relation with electricity demand<sup>10</sup>. The income per capita data will be collected from World Bank data source<sup>11</sup>.

#### Proportion of industry and construction sectors's electricity consumption in total

The 2017 report of EVN highlighted a rapid increase of proportion in total of electricity consumption needed for the industry, and construction sectors. It has been recorded to increase from 46.7% in 2005 to 51.9% in 2010, and to 54.77% in 2015. Also, it is remarked that the growth rate in the duration of 2010-2015 is lower than the ones recorded in the previous duration (2005-2010). However, the industry and construction sectors are still acting as the leading sector and contribute at a highest level in comparison with other sectors in economics. Data relevant to proportion of electricity consumption of industry and construction sectors are be referred from the PDP.VII rev.

### Electric tariff

Electric tariff is an essential condition which impacts directly on every production in economics. In other words, electric tariff plays as a major input manufacturing cost of all sectors in economics. A number of studies on the impacts of electric tariff onto consumption behaviors have already been deployed in the last decades. However, it is really difficult to get an unanimity between those studies as the tariff policy is differed from countries to countries. Vietnam's electric tariff is identified as the lowest fare level in region and worldwide. Data involving national electric tariff will be obtained from EVN's database<sup>9</sup>.

#### Collecting data in time series of 1990 to 2015

After analyzing factors which could make influence on the electricity consumption of industry and construction sectors in Vietnam, then the historical records of those factors are assembled from various

database sources. The more sufficient, reliable and long enough data, the more accurate forecasted results are. With a given time series data and  $k$  represents for an independent variable of prediction model, then  $(n - k) > 20$ <sup>12,13</sup>.

In this paper, GDP of industry and construction sectors, the proportion of industry and construction sectors in entire economics, income of person, and electric tariff will be brought into forecasting model as independent variables. Four independent variables will lead to  $n > 20 + 4$ .

In this paper, historical data from 1990 to 2015 are assembled and constructed as a time series order. This selected 26 values (equivalent to 26 years) time series is relatively long enough to be tested. The collected data are shown in **Table 1**.

## RESULTS

### Converting variables into natural logarithms

The input time series data will be converted into natural logarithm forms. Converted results are shown in **Table 2**.

### Testing

#### Stationary test

A stationary test is conducted to test the stationary characteristics of data. Results shown in **Table 3** indicate that all variables are non-stationary. As shown in **Table 3**, the p-value of almost variables are higher than  $\alpha$  ( $\alpha = 0.05$ ). The only variable has the p-value of lower than 0.05 is the GDP of industry and construction sectors [ $\ln(G_t)$ ]. As all variables are non-stationary, a co-integration test will be employed to be conducted instead of computing a first difference calculation.

#### Co-integration test

Results of co-integration test are performed in **Table 4**. The T-test results indicate that there are only four co-integration variables at the value of 0.05. It is corresponding to the four mentioned non-stationary time series data.

### $R^2$ and p-value testing

After conducting co-integration test, the coefficients of equation (2) are computed. Calculated results are performed in **Table 5**. The condition for choosing the coefficients of equation is that the  $R^2$  value is approximately 1 and p-value of all variables are less than 0.05. **Table 5** shows the value of  $R^2$  testing of 0.992581.

It means that 99.3% of dependent variables have impacts on independent ones. However, as p-value of  $\ln P_t$  is above 0.05,  $\ln P_t$  is eliminated. Then all coefficients of equation will be recalculated in second time. Recalculated results are shown in **Table 6**; in which p-value of all variables are less than 0.05.

### Eliminating inappropriate variables

As  $\ln P_t$  is eliminated, the equation (2) become:

$$\ln EC_t = \beta_0 + \beta_1 \ln G_t + \beta_2 \ln I_t + \beta_3 \ln X_t \quad (4)$$

With  $\beta_0$ ,  $\beta_1$ ,  $\beta_2$ , and  $\beta_3$  are -5.05, 0.372, 0.623, and 1.864, respectively. Then the equation (4) becomes:

$$\ln EC_t = -5.05 + 0.372 \ln G_t + 0.623 \ln I_t + 1.864 \ln X_t \quad (5)$$

That equation (5) is the qualified equation for forecasting.

### Comparison to historical data and evaluating MAPE

The equation (5) is launched to recalculate the electricity consumption in the past. Results are brought into a comparison with historical data to evaluate the accuracy of forecasting. Then a MAPE testing is applied with results are shown in **Table 7**. It is realized that the MAPE has a value of 7.66%. This value is noticeable as it is much lower than usual MAPE errors for long-term forecasting<sup>14</sup>. Therefore, if there is no significant fluctuation in economics and society, then the equation (5) could be a feasible forecasting tool for national power system.

### Forecast on electricity consumption of industry and construction sectors to 2030

Forecasted value of GDP of industry and construction sectors, proportion of industry and construction sectors in entire economics, and income per capita of Vietnam to 2030 are collected and listed in **Table 8**<sup>9</sup>. As mentioned processing, those data will be converted into its corresponding natural logarithms. Then the equation (5) is applied to forecast the electricity consumption of Vietnam's industry and construction sectors in the future. Forecasted results are shown in **Table 9**.

The results show that: (1) in the low scenario, the electricity demand of the industry and construction sectors will reach 111,039 GWh, 167,945 GWh, and 227,634 GWh in 2020, 2025, and 2030, respectively; (2) the forecasted values of the base scenario are 112,853 GWh in 2020, 172,691 GWh in 2025, and 242,027 GWh in 2030; and (3) the corresponding predictions for high scenario in 2020, 2025, and 2030 are 115,947 GWh, 181,591 GWh, and 257,272 GWh, respectively. The values in high scenario in this study

**Table 1: Units for Magnetic Properties**<sup>9-11</sup>

Year	Electricity consumption	GDP of the sector	Proportion consumption of the sector	Income	Electric price
	GWh	Billion US\$	%	US\$/person	VNĐ/kWh
1990	2,845	1,467.4	46.0	130	640.0
1991	3,080	2,287.4	46.8	110	640.0
1992	3,197	2,690.1	46.1	130	640.0
1993	3,477	3,809.3	44.4	170	645.0
1994	3,944	4,701.6	42.5	200	645.0
1995	4,614	5,962.9	41.3	260	651.0
1996	5,503	7,330.7	41.1	310	667.0
1997	6,163	8,610.1	40.3	350	673.0
1998	6,781	8,840.7	38.4	360	684.0
1999	7,590	9,894.4	38.7	370	700.0
2000	8,743	11,504.3	41.6	400	718.0
2001	10,503	12,514.3	40.6	430	742.0
2002	12,681	13,547.1	41.9	460	752.0
2003	15,290	15,665.7	43.8	510	761.0
2004	17,896	18,508.8	45.1	590	774.0
2005	21,302	21,976.2	46.7	680	783.0
2006	24,290	25,609.3	47.4	760	789.0
2007	29,212	29,813.6	50.0	850	842.0
2008	34,156	36,755.2	50.7	1,000	948.5
2009	38,504	39,637.0	50.6	1,120	970.9
2010	44,428	37,251.1	51.9	1,270	1,058.0
2011	50,085	43,703.9	52.9	1,390	1,242.0
2012	55,300	52,289.8	52.4	1,550	1,437.0
2013	60,773	56,828.7	52.7	1,740	1,508.8
2014	69,185	61,846.7	53.9	1,900	1,508.8
2015	76,795	64,252.8	52.6	1,990	1,622.0

**Table 2: Converted results into natural logarithms**

	$\ln(EC_t)$	$\ln(G_t)$	$\ln(X_t)$	$\ln(I_t)$	$\ln(P_t)$
1990	7.95	7.29	3.83	4.87	6.46
1991	8.03	7.74	3.85	4.70	6.46
1992	8.07	7.90	3.83	4.87	6.46
1993	8.15	8.25	3.79	5.14	6.47
1994	8.28	8.46	3.75	5.30	6.47
1995	8.44	8.69	3.72	5.56	6.48
1996	8.61	8.90	3.72	5.74	6.50
1997	8.73	9.06	3.70	5.86	6.51
1998	8.82	9.09	3.65	5.89	6.53
1999	8.93	9.20	3.66	5.91	6.55
2000	9.08	9.35	3.73	5.99	6.58
2001	9.26	9.43	3.70	6.06	6.61
2002	9.45	9.51	3.74	6.13	6.62
2003	9.63	9.66	3.78	6.23	6.63
2004	9.79	9.83	3.81	6.38	6.65
2005	9.97	10.00	3.84	6.52	6.66
2006	10.10	10.15	3.86	6.63	6.67
2007	10.28	10.30	3.91	6.75	6.74
2008	10.44	10.51	3.93	6.91	6.85
2009	10.56	10.59	3.92	7.02	6.88
2010	10.70	10.53	3.95	7.15	6.96
2011	10.82	10.69	3.97	7.24	7.12
2012	10.92	10.86	3.96	7.35	7.27
2013	11.01	10.95	3.96	7.46	7.32
2014	11.14	11.03	3.99	7.55	7.32
2015	11.25	11.07	3.96	7.60	7.39

**Table 3: Stationary test of forecasting equation**

Variable	ADF Test		P-P Test	
	T. statistic	Prob. value	T. statistic	Prob. Value
$\ln EC_t$	-0.556033	0.8630	0.419163	0.9797
$\ln G_t$	-4.154082	0.0037	-4.154082	0.0037
$\ln I_t$	-2.815066	0.0711	-0.475247	0.8805
$\ln X_t$	-2.271965	0.1893	-0.395858	0.8955
$\ln P_t$	2.593966	1	2.324744	0.9999

**Table 4: Co-Integration test**

Hypothesized	Trace Statistic	Critical Value	Prob.
None *	107.4064	69.81889	0.0000
At most 1 *	68.64893	47.85613	0.0002
At most 2 *	37.34043	29.79707	0.0056
At most 3 *	15.94579	15.49471	0.0427
At most 4	2.010153	3.841466	0.1562

**Table 5: Results of the first calculation**

Variable	Coefficient	Std. Error	t-Statistic	Prob.
C	-4.798612	1.197327	-4.007772	0.0006
$\ln G_t$	0.339614	0.165795	2.048397	0.0500
$\ln I_t$	0.686921	0.241594	2.843290	0.0097
$\ln P_t$	-0.093344	0.218511	-0.427181	0.6736
$\ln X_t$	1.941250	0.328647	5.906802	0.0000
$R^2$		0.992581		

**Table 6: Results of the second calculation**

Variable	Coefficient	Std. Error	t-Statistic	Prob.
C	-5.050521	1.022495	-4.939411	0.0001
$\ln G_t$	0.372298	0.144326	2.579560	0.0171
$\ln I_t$	0.623799	0.187552	3.326022	0.0031
$\ln X_t$	1.864202	0.269579	6.915226	0.0000
$R^2$		0.992516		

are less than from 9.0% to 15.8 % of that of the based of in the Revised version of master plan N0. VII<sup>9</sup>.

## CONCLUSION & DICUSSION

In this paper, an econometric model namely Cobb Douglas production function has been applied to forecast the electricity consumption of Vietnam's industry and construction sectors to 2030. Four variables have been identified as: (1) GDP of industry and construction sectors; (2) income per person; (3) proportion of the industry and construction sectors in entire economics (GDP); and (4) electricity price. Three testing methods have been launched to build the most reliable and highest accuracy prediction equation, they are: (1) stationary testing; (2) co-integration testing; and (3)  $R^2$  and p-value testing. The equation (5) has the MAPE has a value of 7.66%. This value is a very good MAPE error for long-term forecasting. There are three qualified variables (GDP of the industry and construction sectors, proportion

of industry and construction sectors in entire economics and income per person) have been figured-out. It means that the electricity price has no impacts on the electricity consumption behaviors of Vietnam's industry and construction sectors. It can be explained that Vietnam's electricity tariff has been fixed based on national policy. Additionally, there is a number of manufacturing industries is currently provided with special subsidy-tariff policies. The demand of Vietnam's the industry and construction sectors in 2030 will be doubled in comparison with the values of 2020 and tripled to the consumption of 2016 (85,305 GWh). For this reason, it is an urgent issue to release an appropriate investment on national power system. Moreover, variable of electric price does not effect to the demand. This is a very critical result of the study for authority governors in Vietnam.

There is very common that forecating of MOIT (PDP.VII rev.) are always higher than real one.

**Table 7: Results of the mape testing for the forecasting equation (5)**

Year	Consumption by euqation (5)	Historical data of con- sumption	Error
Unit	GWh	GWh	%
1990	2,530.755	2,845	11,0
1991	2,777.509	3,080	9,8
1992	3,183.654	3,197	0,4
1993	3,994.011	3,477	-14,9
1994	4,406.035	3,944	-11,7
1995	5,374.738	4,614	-16,5
1996	6,418.859	5,503	-16,6
1997	7,086.356	6,163	-15,0
1998	6,656.287	6,781	1,8
1999	7,163.889	7,590	5,6
2000	9,101.820	8,743	-4,1
2001	9,389.121	10,503	10,6
2002	10,696.150	12,681	15,7
2003	13,078.730	15,290	14,5
2004	16,094.380	17,896	10,1
2005	20,003.750	21,302	6,1
2006	23,335.400	24,290	3,9
2007	29,250.450	29,212	-0,1
2008	35,912.550	34,156	-5,1
2009	39,496.170	38,504	-2,6
2010	43,764.510	44,428	1,5
2011	50,915.380	50,085	-1,7
2012	57,235.370	55,300	-3,5
2013	64,131.260	60,773	-5,5
2014	72,913.230	69,185	-5,4
2015	72,736.170	76,795	5,3
MAPE			7.66

## ABBREVIATION

GDP: Gross Domestic Production

EVN: Vietnam Electricity

MOIT: Ministry of Industry and Trade

PDP.VII rev.: Revised version of Master Plan N0. VII for Power System in Vietnam

MAPE: Mean Absolute Percentage Error

ANN: Artificial Neural Networks

ADF: Augmented Dickey Fuller

P-P: Phillips-Perron

## CONFLICT OF INTEREST

Group of authors have no conflict on interest in publishing of the paper.

**Table 8: Forecasted values of the proportion in GDP of the sectors in total, and income per person to 2030<sup>9</sup>**

Variable	Scenario	2020	2025	2030
Income per person [US\$/yr]	Low Scenario	3,307	4,939	7,205
	Base Scenario	3,370	5,111	7,836
	High Scenario	3,485	5,450	8,450
Proportion of the sectors [%]		55.48	60.35	62.39
GDP of the sectors [%]	Low Scenario	65,428	66,603	67,779
	Base Scenario	66,212	67,779	69,424
	High Scenario	67,309	69,659	72,089

**Table 9: Forecast on the electricity consumption of the sectors to 2030 [GWh]**

	2020	2025	2030
Low Scenario	111,039	167,945	227,634
Base Scenario	112,853	172,691	242,027
High Scenario	115,947	181,591	257,272
Revised version of master plan n0. VII <sup>9</sup>			
Base Scenario	127,380	206,446	305,712

## AUTHOR CONTRIBUTION

Viet-Cuong VO, who deliver ideal, method, and data of the study. Correcting the manuscript.

Hoang-Phuong NGUYEN, who running the program.

Le-Duy-Luan NGUYEN, who draft the manuscript.

Van-Hung PHAM, who do the first try of the program.

## REFERENCES

1. Vietnam Electricity (EVN), Vietnam Power 2015 Report. 2015;.
2. Ozoh P, Abd-Rahman S, Labadin J, Apperley M. A Comparative Analysis of Techniques for Forecasting Electricity Consumption. *International Journal of Computer Applications*. 2014;88(15). Available from: <https://doi.org/10.5120/15426-3841>.
3. Husain S, Islam MS. A Test for the Cobb Douglas Production Function in Manufacturing Sector: The Case of Bangladesh. *International Journal of Business and Economics Research*. 2016;5(5):149–154. Available from: <https://doi.org/10.11648/j.ijber.20160505.13>.
4. Imtiaz AK, Norman BM, Amran MR, Saleem M, Wahab NIA, Mohibullah. Evaluation and Forecasting of Long Term Electricity Consumption Demand for Malaysia by Analysis. *The First International Power and Energy Conference PECon 2006, Putrajaya, Malaysia*. 2006;Available from: <https://doi.org/10.1109/PECON.2006.346658>.
5. Muhammad S, Hooi HL. The dynamics of electricity consumption and economic growth: A revisit study of their causality in Pakistan. *Energy*. 2012;39:146–153. Available from: <https://doi.org/10.1016/j.energy.2012.01.048>.
6. Jiahai Y, Changhong Z, Shunkun Y, Zhaoguang H. Electricity consumption an economic growth in China: Cointegration and co-feature analysis. *Energy Economics*. 2007;29:1179–1191. Available from: <https://doi.org/10.1016/j.eneco.2006.09.005>.
7. Nguyen VMH, Nguyen KTP, Vo CV, Phan BTT. Forecast on 2030 Vietnam Electricity Consumption. *Engineering, Technology & Applied Science Research*. 2018;8(3):2869–2874. Available from: <https://doi.org/10.1109/ICELTICS.2017.8253238PMCid:PMC5341203>.
8. Robert FE, Granger CWJ. Co-integration and Error Correction: Representation, Estimation, and Testing. *Econometrica*. 1987;55(2):251–276. Available from: <https://doi.org/10.2307/1913236>.
9. Institute of Energy, MOIT, "Revised version of master plan N0. VII for power system in Vietnam". 2016;.
10. General Statistics Office of Vietnam, "Master investigation on populayion and households 2014 - Vietnam". 2014;.
11. Data world bank;Available from: <http://data.worldbank.org/country/vietnam>.
12. Green SB. How many subjects does it take to do a regression analysis? *Multivariate Behavioral Research*. 1991;26:499–510. PMID: 26776715. Available from: [https://doi.org/10.1207/s15327906mbr2603\\_7](https://doi.org/10.1207/s15327906mbr2603_7).
13. Barbara GT, Linda SF. Using multivariate statistics 5th Edn. California State University, Northridge, Pearson Education Inc. 2007;.
14. Amstrong, Scott J. Long-Range Forecasting: From Crystal Ball to Computer. Wiley-Interscience; Second edition. 1985;.

# Mô hình kinh tế lượng dự báo nhu cầu điện năng của ngành công nghiệp và xây dựng tại Việt Nam đến 2030

Võ Viết Cường<sup>1,\*</sup>, Nguyễn Hoàng Phương<sup>1,2</sup>, Nguyễn Lê Duy Luân<sup>3</sup>, Phạm Văn Hùng<sup>1</sup>



Use your smartphone to scan this QR code and download this article

## TÓM TẮT

Dự báo chính xác nhu cầu điện dài hạn có vai trò rất quan trọng cho quy hoạch hệ thống điện tại bất kỳ quốc gia nào. Việt Nam là một trong những nước có kinh tế phát triển nhanh nhất thế giới, nhu cầu điện tăng trung bình khoảng 15%/năm trong suốt ba thập kỷ vừa qua. Sự đóng góp của ngành công nghiệp và ngành xây dựng trong GDP tăng đều qua các năm, và hiện đang giữ tỷ trọng lớn nhất trong tiêu thụ điện với tỷ lệ trên 50% phụ tải quốc gia. Làm sao để xác định chính xác tiêu thụ điện của những lĩnh vực trên góp phần quan trọng cho việc quy hoạch hệ thống điện. Bài báo này đề xuất áp dụng mô hình kinh tế lượng với hàm sản xuất Cobb Douglas để dự báo nhu cầu điện của ngành công nghiệp và ngành xây dựng Việt Nam tới năm 2030. Bốn biến được sử dụng là giá trị trong GDP của hai ngành trên, thu nhập đầu người, tỷ trọng điện năng tiêu thụ của 2 ngành trong tổng nhu cầu của nền kinh tế, và giá điện. Kết quả dự báo cho thấy phương pháp đề xuất có sai số MAPE ở mức khá thấp là 7,66%. Biến giá điện không tác động đến nhu cầu điện của 2 ngành. Đây là kết quả có giá trị của nghiên cứu cho các nhà quản lý tại Việt Nam. Nhu cầu điện theo kịch bản cơ sở của GDP và thu nhập đầu người được dự báo lần lượt là 112.853 GWh, 172.691 GWh, và 242.027 GWh tương ứng với các năm 2020, 20205, và 2030. Với kịch bản cao, nhu cầu tương ứng là 115.947 GWh, 181.591 GWh, và 257.272 GWh. Những giá trị của kịch bản cao thấp hơn từ 9,0% đến 15,8% so với giá trị tương ứng trong kịch bản cơ sở của Tổng Sơ đồ 7 hiệu chỉnh.

**Từ khóa:** Dự báo, Mô hình kinh tế lượng, Nhu cầu điện, Hàm sản xuất Cobb Douglas, Ngành công nghiệp & xây dựng

<sup>1</sup>Trường Đại học Sư phạm Kỹ thuật Tp. HCM, Số 1, Võ Văn Ngân, Quận Thủ Đức, Tp. HCM, Việt Nam

<sup>2</sup>Trường Đại học Tiền Giang, Số 119, Ấp Bắc, Phường 5, Tp. Mỹ Tho, Tỉnh Tiền Giang, Việt Nam

<sup>3</sup>Trường Đại học Kiến trúc Tp. HCM, Số 196, Pasteur, Quận 3, Tp. HCM, Việt Nam

## Liên hệ

**Võ Viết Cường**, Trường Đại học Sư phạm Kỹ thuật Tp. HCM, Số 1, Võ Văn Ngân, Quận Thủ Đức, Tp. HCM, Việt Nam

Email: cuongvv@hcmute.edu.vn

## Lịch sử

- Ngày nhận: 15-12-2019
- Ngày chấp nhận: 13-3-2020
- Ngày đăng: 31-3-2020

DOI: 10.32508/stdjet.v3i1.646



## Bản quyền

© ĐHQG Tp.HCM. Đây là bài báo công bố mở được phát hành theo các điều khoản của the Creative Commons Attribution 4.0 International license.



**Trích dẫn bài báo này:** Viết Cường V, Hoàng Phương N, Lê Duy Luân N, Văn Hùng P. **Mô hình kinh tế lượng dự báo nhu cầu điện năng của ngành công nghiệp và xây dựng tại Việt Nam đến 2030.** *Sci. Tech. Dev. J. - Eng. Tech.*; 3(1):316-325.